

RESEARCH DEPARTMENT

BODMIN V.H.F. RELAY STATION: SUMMARY OF INSTALLATION

Technological Report No. RA-2/7
UDC 621.396.712 1967/45

This Report is the property of the British Broadcasting Corporation and may not be reproduced in any form without the written permission of the Corporation.

This Report uses SI units in accordance with B.S. document PD 5686.

R.D.C. Thoday, A.M.I.E.R.E.
J.P. Crean

H Page
for Head of Research Department




Fig.1 General arrangement of aerials on wooden support poles

V.H.F. RELAY STATIONS : SUMMARY OF INSTALLATION
TELEVISION

NAME: BODMIN

SERVICE TRANSMISSIONS COMMENCED: 19th September 1966

SITE DATA

LOCATION: 0.48 km (0.3 miles) North of Bodmin

GRID REFERENCE: SX 071675

HEIGHT, A.O.D.: 122m (400 ft)

SUPPORT STRUCTURE

TYPE: Wooden Poles

OVERALL HEIGHT: 14.3m (47 ft)

GENERAL ARRANGEMENT

FIGURE: 1

FREQUENCIES

BAND: 1

CHANNEL: 5

VISION CARRIER OFFSET: -16.875 kHz

SOUND CARRIER OFFSET: -20 kHz

TRANSMITTER

POWER: 10W (Translator)

NOTES:

1. Detailed information is given on the following drawings held by BBC Transmitter Planning and Installation Department:
PID 6047.2.142A4 Arrangement of Transmitting Aerials on Wooden Pole
PID 6047.2.143A4 Arrangement of Receiving Aerials on Wooden Pole
PID 8732.2.3J Band I Transmitting Dipole, Type H.P.N.
PID 8732.2.4A2 Band I Receiving Yagi, Type 353P

TRANSMITTING AERIAL

DESCRIPTION: Two horizontal $\lambda/2$ dipoles per tier

NUMBER OF TIERS: 2

MEAN HEIGHT: 13.1m (43 ft)

FEEDERS

TRANSMITTING: RPC 2603

RADIATION CHARACTERISTICS

POLARIZATION: Horizontal

MEAN E.R.P.: 7.6W

MAXIMUM E.R.P.: 10.2W

H.R.P.: Fig. 2

PROGRAMME SOURCE

PARENT: Redruth
Obtained by direct reception




Fig.2 Band I templet and horizontal radiation pattern

———Maximum permissible E.R.P.

-----Minimum desirable E.R.P.

Unit field corresponds to an E.R.P. of 100 W